

## Copper flexible laminated connectors

### Product information

Other dimensions or customized parts on request



### Dimension and technical specification

Part-No.	Type	Width mm	Nominal current [A] 65°C bar temp.	Weight per Set [kg]	No. per Set
C-DB-038.0490.220	DBCUC 38/5/60/220/S	38	490	2.00	3
C-DB-048.0590.220	DBCUC 48/5/60/220/S	48	590	2.50	3
C-DB-038.0720.250	DBCUC 38/10/60/250/S	38	720	3.75	3
C-DB-048.0860.250	DBCUC 48/10/60/250/S	48	860	4.50	3
C-DB-058.0990.310	DBCUC 58/10/80/310/S	58	990	6.50	3
C-DB-078.1240.310	DBCUC 78/10/80/310/S	78	1240	8.50	3
C-DB-098.1490.350	DBCUC 98/10/60/350/S	98	1490	11.25	3
C-DB-118.1710.350	DBCUC 118/10/100/350/S	118	1710	14.00	3

### Applications:

- Connection between motors- and machine parts
- Expansion connectors between bar systems
- Connection as earthing tapes
- Connection between electrodes and busbars in electrolyse applications
- Connection for generator, transformers and MCC Systems
- Connections for movable parts
- Connection for switchgear applications

All information without guarantee